

Wibroplast

Plasticizing admixture for vibropressed elements.

Description	Characteristics
 Description It's plasticizing admixture, produced on basis of surfactants. Created a homogeneous cement paste is characterized by small forces of internal friction. Extends the life of machinery and equipment used in production. Reduces efflorescence of calcium. Improves the appearance of the surface. 	 Natur: homogeneous liquid Colour: beige, uniform Density:1,05 ± 0,03 g/cm³ pH: 7,0-8,0
• It seals and compacted concrete mix.	

 Application Scope of application concrete paving stones palisade, concrete vertebrae concrete flowerpots curbstones paving slabs small concrete architectural elements we do not recommend dosing mixture to the dry ingredients 	It's completely soluble in water. It could be added to the water before mixing or directly to the mixer. The amount of water is defined in depend of required consistency. The optimum dosage is experimentally determined taking into account the required properties of concrete and hardened concrete. Precautions
Method of use Granice dozowania od 0,3% do 0,8% domieszki do masy cementu.	 Protection from sunlight, store at temperatures above 0°[C]. Shelf life: 12 months.



Wibroplast

Plasticizing admixture for vibropressed elements.

Safety

Wibroplast is a product classified as « harmless». It is recommended to wear the normal protective equipment. For further information, please refer to the safety data sheet.



The information contained in this document is given to the best of our knowledge and the results from extensive testing. However, it cannot, in any case be considered as a warranty involving our liability in case of misuse. Tests should be carried out before any use of the product to ensure that the methods and conditions of use of the product are satisfactory. Our specialists are at the disposal of the users in order to help them with any problem encountered.